



**FAIRBURNS
GROUP**

Total Electrical Solutions

Nelson 16 XL110 - LED Bollard

The *Nelson 16 XL100 LED Bollard* is an environmentally friendly, energy saving replacement for traditional sodium, mercury and halogen style bollards.



The Nelson 16 XL100 LED Bollard is simply styled and designed to suit most architectural fittings. It is ideal for pedestrian walkways, precincts, squares, public and private gardens.

Durable extruded aluminium body and polycarbonate lens providing good levels of vandal resistance.

Black polyester coated finish providing a hard wearing decorative finish.

Sealed to IP55 with silicone gasket seal.

Available root or flange plate mounted.



Specifications: Nelson 16 XL110 – LED Bollard

	AC
Product Code	NB16-A001-C2 / FE
Power Consumption LED's	18.24 Watts
Power Consumption Driver	4.5 Watts
Total Power Consumption	22.74 Watts
Input Voltage	90 – 264Vac
Input Frequency	47 – 63Hz
Total LED output	1760 Lumens
Efficiency (Typ.)	85%
LED Colour	White (Standard)
Colour Temp (K)	6000 - 7200 degrees K (Standard)
CRI	Ra>70
LED Lifespan	50,000 > 80,000 Hours
Operating Temperature	-30 degrees C to + 50 degrees C
Working Humidity	0 ~ 95%
Turn on time	100ns
Product Size (mm)	1000mm x 186mm
Material	Aluminium Body and Polycarbonate Lens
Net Weight	6.5 Kg
Mounting	Root Mounted as standard. Flange Plate available.
Protection Rate	IP55
Certification	RoHS, CE
Warranty	3 Years

**FAIRBURNS GROUP
LIMITED**

73 – 79 Clarence Street
Hull
HU9 1DH

Tel: +44 (0) 1482 323 352

Fax: +44 (0) 1482 229 873

